

Przelicznik wagowy zestawów śrubowych HV

Śruba HV z powiększonym łbem do połączeń wstępnie sprężanych klasa 10.9 - ocynk ogniowy								
DIN 6914	PN-82343	PN-EN 14399-4						
Wielkość orientacyjna - masa w kg/1000 szt. przy 7,85 kg/dm ³								
d/l	M 12	M 16	M 20	M 22	M 24	M 27	M 30	M 36
30	48							
35	52							
40	56	105						
45	59	113	180					
50	64	121	194	249				
55	68	129	207	264				
60	72	137	219	279	353			
65	77	145	232	294	371			
70	81	153	244	309	389	519		
75	86	157	257	324	407	542	695	
80	90	165	269	339	425	564	723	
85	95	173	282	354	443	587	751	1186
90	99	181	288	363	449	609	779	1226
95	104	189	301	378	467	632	807	1266
100		197	313	393	485	645	832	1303
105		205	326	408	503	666	860	1343
110		213	338	423	521	687	888	1383
115		221	351	438	539	708	916	1423
120		229	363	453	557	729	944	1463
125		237	376	468	575	750	972	1503
130		245	388	483	593	771	1000	1543
135			400	498	611	792	1028	1583
140			413	513	629	813	1055	1623
145			425	528	647	834	1083	1663
150			438	543	665	855	1110	1703
155			450	558	683	876	1138	1743
160				573	700	897	1168	1783
165				588	718	918	1194	1823
170					736	939	1222	1863
175					754	960	1256	1903
180					772	981	1284	1943
185					790	1000	1312	1983
190					808	1020	1340	2023
195					826	1040	1368	2063
200						1060	1396	2103

EURO-MET

— ■ technika zamocowań ■ elementy złączne ■ —



infolinia: 801 555 280

www.euro-met.pl

www.e-sruby.com.pl